

TPP-1

50kg Capacity



SINGLE POINT

APPLICATIONS

Bech platform up to 600x600 mm.
Hopper weighing

FEATURES

Single point load cell.
Bending beam load cell.
Fully stainless steel construction.
3000 divisions OIML R60 Class C.
Direct platform mounting.
High accuracy with off-center loads.
Low profile.
Protected against humidity IP67 (EN60529).





3000d OIML Certificate No.R60/1991-GB1-96-02



C3

SPECIFICATIONS

Nominal capacities (LN)	50 kg
Accuracy class	3000 n. OIML
Minimum dead load	0 %Ln
Service load	150 %Ln
Safe load limit	200 %Ln
Maximum combined error	0,017 %Sn
Repeatability error	0.015 %Sn
Temperature effect:	0.01 %Sn/5°C
On zero on sensitivity:	0.006 %Sn/5°C
Creep error	0.016 %Sn
Temperature compensation	-10..40 °C
Temperature limits	-20..50 °C
Nominal sensitivity	2±0.1% mV/V (2)
Nominal input voltage	10 V (2)
Maximum input voltage	15 V (2)
Input impedance	386Ω±2%
Output impedance	350±3Ω
No load output (SN)	2 %Sn
Insulation resistance	> 5000 MΩ
Maximum deflection	0.2-0.6
Cable length	5 m



Dimensions (mm)

Reference	Nominal capacities - Ln (kg)	Accuracy class n. OIML	y = emax / vmin	#Code
TPP-1/50	50	C3	12500	710235