

# KMP-B

PANEL TYPE WEIGHT INDICATOR

## Dozajlama indikatörü

Dozajlama uygulamaları için geliştirilmiş 5 inç dokunmatik ekranlı kolay parametre ayarlarına sahip yüksek hassasiyet oranlı bir kontrol cihazıdır.

20adet reçete kayıt imkanı 8-16 veya 24 malzeme alabilme özelliği USB flaş disk kayıt tutabilme imkanı sunar PLC ve panel kullanmanıza gerek kalmaz

### SPECIFICATIONS

- 8-16-24 pcs Relay Output (Option)
- Remote Display Output (Standard)
- Modbus RTU
- 0-10V /4-20mA Analogue Output (Option)
- Ethernet TCP (Option)
- 3840 measurements per second
- Stability and Absolute Zero indicators
- Small plastic or metal case
- 5 inc touch Display 600x800



### TECHNICAL SPECIFICATIONS

DEVICE	
Screen	5 Inch touch Display
A/D CONVERTER	
Screen	5 Inch touch Display
A/D Converter	24 bit delta
Minimum Input	0.02uV/Division
Analogue Input Range	1mV/V - 10mV/V
Loadcell Input	350-1000 Ohm (Maximum 10 Loadcell)
Internal Resolution	24bit / 16.000.000
Measurement Speed	3840 samples/second
Loadcell Excitation	5Vdc
CALIBRATION	
Calibration Types	Load calibration or Digital mV/V calibration
INPUTS/OUTPUTS	
Outputs	12pcs 10A/250V (Optional hardware)
Inputs	12pcs optically isolated digital inputs (Standard hardware)
Options	4/20mA - 0/10V Analogue Output (Optional hardware) EthernetIP, ModbusTCP
COMMUNICATON	
Communication	1 pcs RS232 or RS485 selectable serial output. 1200-115200bps 1 pcs standard RS232 serial output. 1200-115200bps Modbus RU/ASCII communication USB, Ethernet Modbus TCP/IP
WORKING CONDITIONS	
Voltage/ Power	24Vdc (+/- % 10) / 5W maximum
Working Temperature	-20/70°C
Protection Class	IP54

