



## TECHNICAL SPECIFICATIONS

### DEVICE

Screen 5 Inch touch Display

### A/D CONVERTER

Minimum Input 0.02uV/Division

Analogue Input Range 1mV/V - 10mV/V

Loadcell Input 350-1000 Ohm (Maximum 10 Loadcell)

Internal Resolution 24bit / 16.000.000

Measurement Speed 3840 samples/second

Loadcell Excitation 5Vdc

### CALIBRATION

Calibration Types Load calibratlon or Digital mV/V calibration

### INPUTS/OUTPUTS

Outputs 12pcs 10A/250V (Optional hardware)

Inputs 12pcs optically isolated digital inputs (Standard hardware)

Options 4/20mA - 0/10V Analogue Output (Optional hardware)

EthernetIP, ModbusTCP

### COMMUNICATON

Communication 1 pcs RS232 or RS485 selectable serial output. 1200-115200bps

1 pcs standard RS232 serial output. 1200-115200bps

Modbus RU/ASCII communication

USB, Ethernet Modbus TCP/IP

### WORKING CONDITIONS

Voltage/ Power 24Vdc (+/- % 10) / 5W maximum

Working Temperature -20/70°C

Protection Class IP54

## KMP-C PANEL TYPE WEIGHT INDICATOR

### Randıman Kantarı İndikatörü

Randıman kantaları geliştirilmiş 5 inç dokunmatik ekranlı kolay parametre ayarlarına sahip yüksek hassasiyet oranlı bir kontrol cihazıdır.

5inç ekran arayüzünde anlık tartım, ton / saat günlük aylık ve yıllık toplamları görebilirsiniz PLC ve panel kullanmanız gereklidir.

### SPECIFICATIONS

- 12 pcs Relay Output (Option)
- Remote Dsplay Output (Standard)
- Modbus RTU
- 0-10V /4-20mA Analogue Output (Option)
- Ethernet TCP (Option)
- 3840 measurements per second
- Stability and Absolute Zero indicators
- Small plastic or metal case
- 5 inc touch Display 600x800

