

KMP-D

PANEL TYPE WEIGHT INDICATOR

Çift Kefeli Dolum indikatörü

Çift kefeli torba dolum makinaları için geliştirilmiş 5 inç dokunmatik ekranlı çift load cell girişli her iki kefe içinde ayrı ayrı dolum parametrelerine sahip yüksek hassasiyet oranlı bir kontrol cihazıdır

Hızlı ve yavaş dolum, torba tutma. Torba sallama, torba sayma, gibi özelliklere sahip olduğu için PLC ve panel kullanmanıza gerek kalmaz

SPECIFICATIONS

- 12 pcs Relay Output (Option)
- Remote Display Output (Standard)
- Modbus RTU/ASCII (Standard)
- 0-10V /4-20mA Analogue Output (Option)
- Ethernet TCP (Option)
- 3840 measurements per second
- Stability and Absolute Zero indicators
- Fast/Slow Filling program, dosage program
- Small plastic or metal case
- 5 inc touch Display 600x800



TECHNICAL SPECIFICATIONS

DEVICE	
Screen	5 Inch touch Display
A/D CONVERTER	24 bit delta
Minimum Input	0.02uV/Division
Analogue Input Range	1mV/V - 10mV/V
Loadcell Input	350-1000 Ohm (Maximum 10 Loadcell)
Internal Resolution	24bit / 16.000.000
Measurement Speed	3840 samples/second
Loadcell Excitation	5Vdc
CALIBRATION	
Calibration Types	Load calibraton or Digital mV/V calibration
INPUTS/OUTPUTS	
Outputs	12pcs 10A/250V (Optional hardware)
Inputs	12pcs optically isolated digital inputs (Standard hardware)
Options	4/20mA - 0/10V Analogue Output (Optional hardware) EthernetIP, ModbusTCP
COMMUNICATON	
Communication	1 pcs RS232 or RS485 selectable serial output. 1200-115200bps 1 pcs standard RS232 serial output. 1200-115200bps Modbus RU/ASCII communication USB, Ethernet Modbus TCP/IP
WORKING CONDITIONS	
Voltage/ Power	24Vdc (+/- % 10) / 5W maximum
Working Temperature	-20/70°C
Protection Class	IP54

