



TECHNICAL SPECIFICATIONS

DEVICE	
Screen	5 Inch touch Display
A/D CONVERTER	
Minimum Input	0.02uV/Division
Analogue Input Range	1mV/V - 10mV/V
Loadcell Input	350-1000 Ohm (Maximum 10 Loadcell)
Internal Resolution	24bit / 16.000.000
Measurement Speed	3840 samples/second
Loadcell Excitation	5Vdc
CALIBRATION	
Calibration Types	Load calibraton or Digital mV/V calibration
INPUTS/OUTPUTS	
Outputs	12pcs 10A/250V (Optional hardware)
Inputs	12pcs optically isolated digital inputs (Standard hardware)
Options	4/20mA - 0/10V Analogue Output (Optional hardware) EthernetIP, ModbusTCP
COMMUNICATON	
Communication	1 pcs RS232 or RS485 selectable serial output. 1200-115200bps 1 pcs standard RS232 serial output. 1200-115200bps Modbus RU/ASCII communication USB, Ethernet Modbus TCP/IP
WORKING CONDITIONS	
Voltage/ Power	24Vdc (+/- % 10) / 5W maximum
Working Temperature	-20/70°C
Protection Class	IP54

KMP-E

PANEL TYPE WEIGHT INDICATOR

Süt soğutma ve yıkama kontrol cihazı

Bu cihaz süt soğutma tankları için geliştirilmiş hem otomatik soğutma yapabilen hem de otomatik yıkama yapabilen bir kontrol cihazıdır. 5 inç dokunmatik ekran ile geniş bir ara yüz kullanım alanı sağlar Kullanıcı ekranda kg litre sıcaklık değerlerine kolayca kontrol eder.

SPECIFICATIONS

- 12 pcs Relay Output (Option)
- Remote Display Output (Standard)
- Modbus RTU/ASCII (Standard)
- 0-10V /4-20mA Analogue Output (Option)
- Ethernet TCP (Option)
- 3840 measurements per second
- Stability and Absolute Zero indicators
- Fast/Slow Filling program,dosage program
- Small plastic or metal case
- 5 inc touch Display 600x800

